



²⁸ PIG® Roof Leak Diverter Bucket Kit

TLS121 Tarp; Hose; Hanging Straps; Container, Install With Hanging Straps, 5' x 5'

Our portable Leak Diverter Bucket Kits are perfect for grab-and-go response to overhead leaks.

- Contains supplies for rapid response to roof leaks, all in a 6.5-gallon pail
- Pail lid has a removable plug to allow the drainage hose to be inserted without having to remove the lid
- Pail can be used as a collection container for diverted liquid; printed "Caution" message doubles as a warning sign
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Translucent material lets light through and allows easy monitoring of leak
- 60"-long adjustable straps allow fast setup and response

Bid	
EXCLUSIVE	

Item#	Description	Dimensions	Weight		
TLS121-TR	Translucent	5' W x 5' L	11 lbs.		
Metric Equivalent:					
Item#	Description	Dimensions	Weight		
TLS121-TR	Translucent	152.4cm W x 152.4cm L	5 kg		
Specifications					
Dimensions		5' W x 5' L			
Brand		PIG			
Contains		Tarp; Hose; Hanging Straps;	Container		
Drainage Hose Included		Yes			
Hanging Straps Included		Yes			
Hose Connector		.75"			
Installation Method		Hanging Straps			

Shape	Square			
Sold as	1 each			
Weight	11 lbs.			
# per Pallet	27			
Composition	Diverter - PVC, Polyester Hose - PVC Straps - Nylon Bucket - Plastic			
Application	Roofs			
Flow Rate	3.33 gal./Minute			
Includes	1 - 5' L x 5' W Leak Diverter 1 - 25' L Clear Drainage Hose (TLS679) 4 - 60" L Adjustable Hanging Straps (TLS559) 1 - 6.5-gal. Bucket			
UNSPSC	24141506			
Pigalog® Page Number	Page 264			
Metric Equivalent				
Dimensions	152.4cm W x 152.4cm L			
Weight	5 kg			
Technical Information				
Technical Documents				
Instructions for Assembling PIG® Leak Diverter System				
Disclaimers				
Maximum Working Temperature				
Not suitable for temperatures over 170°F/77°C.				
Nominal Leak Diverter Dimensions				

Dimensions are nominal size due to pinched corners and reinforced side walls.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com